

4x150W LED - 5,5M









Our engineers know that the market needs a lighting tower that is rugged, long lasting and safe. The X-MINI LED has been created beginning from these characteristics. It is the best solution to your needs and guarantees 2000 sqm of illuminated area. 18 units can be loaded on a standard truck. To all of this, we added the technology that allows for maximum fuel efficiency and reliability.











- Multi-directionally adjustable and tiltable floodlights
- 5 sections galvanized telescopic vertical mast
- Maximum mast height 5,5 m
- Manual lifting system by winch complete with auto-braking system
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 18 units per truck
- Central lifting eye for effective handling
- Hand trolley
- Light weight for improved manoeuvrability
- Simple, rugged machine design and layout
- Certified windstability up to 80 Km/h
- Electrical coiled cable complete with housing
- Guided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against circuit breaker
- On/Off switches-one for each lamp
- Easy acess for maintenance
- 2 extendable & height adjustable galvanized stabilizers

APPLICATIONS



Gas, oil & mining operations



Special events



Rural & hard to reach areas



Emergency response



Construction & work sites




Military applications



Ease of transport and handling







technical data

| Dimensions & weight | |
|---------------------------|----------------|
| Dimensions min. (mm) | 1350x950x2160 |
| Dimensions max. (mm) | 1700x1320x5500 |
| Total weight without fuel | 325 Kg |

| Features | |
|-------------|--------|
| Rotation | - |
| Floodlights | 4x150W |
| Lamps | LED |
| Options | - |

| Alternator | |
|----------------------|----------------|
| Model | Synchronous |
| Frequency (Hz) | 50 |
| Insulation class | Н |
| Degree of protection | IP23 |
| Single phase voltage | 3,5 kVA - 230V |
| Auxiliary outlets | 2,5 KVA |
| | |

| Engine | |
|-------------------------|------------|
| Model | Yanmar L48 |
| Fuel | Diesel |
| r.p.m | 3000 |
| Tank capacity (I) | 2,4 |
| Consumption (I/h) | 0,5 circa |
| Noise level (dBA) at 7m | 75 |

Standard load delivery


18 sets



Units Per Truck

Illuminated area (5 lux min.)

2000 sqm





Lighting Tower Specialist

TRIME s.p.a.

Strada per Robecco, snc 20081 Cassinetta di Lugagnano (MI) Tel. +39 02 942 1724 www.trime.it - info@trime.it