

light on your work

**X-START**  
4x150W LED - 9M



**TRIME**  
Lighting Tower Specialist



## X-START 4x150W LED - 9M

*Our engineers know that the market needs a lighting tower that is rugged, long lasting and safe. The X-START LED has been created beginning from these characteristics. It is the best solution to your needs and guarantees 3000 sqm of illuminated area. 10 units can be loaded on a standard truck. To all of this, we added the technology that allows for maximum fuel efficiency and reliability.*



8,5m



750Kg



340°



3000 sqm



80(l) - 0,55(l/h)

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8,5 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 10 units per truck
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization

## APPLICATIONS



Gas, oil & mining operations



Special events



Rural & hard to reach areas




Emergency response



Construction & work sites



Military applications



Illuminated area  
**3000 sqm**



**Ease of transport  
and handling**



**10  
Units Per Truck**



**You can place 10 units on a  
single vehicle thanks to one  
of the compactest footprints  
on the market.**

## KEY BENEFITS

✓ *Easy to move*

✓ *Robustness*

✓ *Safety*

✓ *Cost effective*


LED TECHNOLOGY

SAFETY VERTICAL MAST

GALVANIZED BODY  
DURABLE ANTI-CORROSION  
PROTECTION

FORK LIFT POCKET

4 ADJUSTABLE  
STABILIZERS





## technical data

Dimensions & weight	
Dimensions min. (mm)	2560x1320x2550
Dimensions max. (mm)	2560x2550x8500
Total weight without fuel	750 Kg

Features	
Rotation	340°
Floodlights	4x150W
Lamps	LED
Options	Homologated road trailer

Alternator	
Model	Synchronous
Frequency (Hz)	50
Insulation class	H
Degree of protection	IP23
Single phase voltage	3,5 kVA - 230V
Auxiliary outlets	1 kVA

Engine	
Model	Kubota Z482
Fuel	Diesel
r.p.m	1500
Tank capacity (l)	80
Consumption (l/h)	0,55
Running time (h)	145
Noise level (dBA) at 7m	65

## Standard load delivery


**10 sets**



Units Per Truck

Illuminated area (5 lux min.)

**3000 sqm**



# TRIME

Lighting Tower **Specialist**

**TRIME s.p.a.**

Strada per Robecco, snc  
20081 Cassinetta di Lugagnano (MI)  
Tel. +39 02 942 1724  
[www.trime.it](http://www.trime.it) - [info@trime.it](mailto:info@trime.it)