BATTERY LINE

designed and created for your needs

LED TECHNOLOGY

3000 sqm
Illuminated area

recharging in 8hrs

36-72h
running time

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

X-ECO BATTERY

4X100W LED - 8,5M
36H 72H

T-ZERO PRO



sustainability

more sustainable and environmentally friendly future

TRIME®
Lighting Towers

BATTERY LINE

X-ECO BATTERY

4X100W LED - 8,5M
36H 72H

T-ZERO PRO

LED TECHNOLOGY

3000 sqm
Illuminated area



ZERO CO_2 **CARBON EMISSION**

100% BATTERY first unique battery driven

ZERO noise

APPLICATIONS

Constructions · Emergency · Events · Military applications

FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5m, 340° rotatable
- Standard timer for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 14 units per truck**
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Certified wind stability up to 110 km/h
- 4 height adjustable stabilizers
- On board levels for guidance during stabilization
- **Running time 36h-72h**
- 24 volt DC Battery
- Floodlights 4x100W
- **Recharging in 12 hours**
- 230V 1PH built-in Battery charger



14 units per truck
Safe packaging and loading allowing quick unloading

Dimensions & weight	
Dimensions min (mm)	**2540x1390x2420 (LxWxH)**
Dimensions max(mm)	**2540x1550x8500 (LxWxH)**
Total weight (kg)	**910 (36H) - 1242 (72H)**
Floodlights	
Type	**Led**
Power (each)	**100W**
Floodlights number	**4**
IP level	**65**
Timer	**Built-in**
Illuminated area (sqm)	**3000**
Mast	
Lifting method	**Hydraulic**
Max Height	**8,5 m**
Max Wind Speed	**110 km/h**
Rotation	**340°**
Safety valve to raise down the must	**yes**
Battery	
Type	**AGM**
Power Battery Pack	**24Vdc 400Ah (36H)** **24Vdc 800Ah (72H)**
Running time	**36 h - 72 h**
Expected battery cycle	**500**
Expected battery life time	**18000 h**
Charging time with floodlights off	**8 h**
Factory options	
Running time	**300 h dimmable configuration**

easy handling & transportability

TRIME® Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.