PLUG-IN LINE

designed and created for your needs

LED TECHNOLOGY

4700 sqm
Illuminated area



linkable towers

complete silence
on work time
8 HOURS A DAY
7 DAYS A WEEK

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

X-CHAIN
4x160W LED - 7m

T-ZERO PRO

more sustainable and environmentally friendly future

TRIME®
Lighting Towers

PLUG-IN LINE

X-CHAIN

4x160W LED - 7m

T-ZERO PRO

LED TECHNOLOGY

4700 sqm

Illuminated area

ZERO emissions | **ZERO noise** | **ZERO fuel costs**



Patented mast emergency system

The first lighting tower in the market that has a patented mast emergency brake system to improve safety of the operators on site
Registration number: 102017000044431

APPLICATIONS

Constructions | Rail mantenance | Emergency | Events | Military applications

FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 5 sections vertical tower 7meters, 340° rotatable
- **Manual lifting system by winch complete with auto-braking system**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions for easy handling & transportability, up to 33 units per truck**
- Light weight for improved manoeuvrability
- Central lifting eye forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against overload
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization
- **Patented mast emergency brake which prevents the falling of the mast in case of cable failure**
- Winch cover
- Top electrical box protection cover
- 2 Retractable galvanized handles
- **Light Sensor as standard feature**
- Bolted Central lifting eye

Dimensions & weight	
Dimensions min (mm)	**1200x800x2340(LxWxH**
Dimensions max(mm)	**1850x1450x7000 (LxWxH)**
Total weight (kg)	**318**
Floodlights	
Type	**Led**
Power (each)	**160W**
Floodlights number	**4**
IP level	**65**
Illuminated area (sqm)	**4700**
Mast	
Lifting method	**Manual**
Max Height	**7 m**
Max Wind Speed	**110 km/h**
Rotation	**340°**
Input&output	
Inlet plug	**32A - 230V**
Outlet socket	**32A - 230V**
General	
Tower lifting metod	**Manual**
Trailer type	**Hand trolley**



33 units per truck
Safe packaging and loading allowing quick unloading

TRIME®
Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.