ENGINE POWERED

designed and created
for your needs

LED TECHNOLOGY
9300 sqm
Illuminated area

145h
running time with only 80L fuel tank

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use



X-START
4x320W - LED - 8M

more sustainable and environmentally friendly future

TRIME®
Lighting Towers

ENGINE POWERED

X-START

4x320W - LED - 8M

LED TECHNOLOGY

9300 sqm

Illuminated area



RUNNING TIME
80 litres tank
145h

NOISE
level 65 dB(A) at 7m

Cost Effective

APPLICATIONS

Constructions · Mining operations · Emergency · Events · Military applications

FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- **Circuit breaker for electrical protection against overload**
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization

Dimensions & weight	
Dimensions min (mm)	**1830x1370x2560 (LxWxH)**
Dimensions max (mm)	**2320x2570x8000 (LxWxH)**
Total weight (kg)	**706**
Floodlights	
Type	**Led**
Power (each)	**320W**
Floodlights number	**4**
Illuminated area (sqm)	**9300**
Mast	
Lifting method	**Manual**
Max Height	**8 m**
Rotation	**340°**
Max Wind Speed	**80 km/h**
Options	**Homologated road trailer**
Alternator	
Model	**Synchronous**
Frequency (Hz)	**50**
Insulation class	**H**
Degree of protection	**IP 23**
Single phase voltage	**3,5kVA - 230V**
Auxiliary outlets	**1 kVA**
Engine	
Model	**Kubota Z482***
Fuel	**Diesel**
r.p.m.	**1500**
Tank capacity (l)	**80**
Consumption (l/h)	**0,55**
Running time	**145 h**
Noise level dB(A) at 7m	**65**

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used

18 units per truck
Safe packaging and loading allowing quick unloading

easy handling & transportability

TRIME® Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.